



A X E Z E

Access Control Systems

#### AR-S- W2-EM

Waterproof Standalone Prox Card Reader w remote for programming  
Anti-Tamper fitted  
Programming card to Add and Remove Cards

#### AR-S-W2-A Weatherproof Reader (EM+HID)


RFID card reader  
Waterproof, rated to IP68  
User capacity: 10,000  
Card Interface: 125KHz EM +/-or HID card  
Remote control for programming  
Wiegand 26 input/output  
Block enrolment

#### AR-S-W2-A works with your electric door strike.

If the door strike is already fitted you can easily install this unit yourself.  
If you need to purchase a door strike, all Security companies and Bunnings sell them and you can install it yourself.  
If you are not a home handyman you can arrange for an electrician, carpenter, security installer to install the system for you.

Additional cards and keyfobs available from Axeze

## AR-S-W Standalone RFID access control system



Appearance: plastic matte technic, durable.

Support Card: 125KHz EM, 125KHz HID, 13.56MHz.

Output Format: 26bit is factory default setting.

For Wiegand 26, reader will output according to card's format automatically.

Ultra-low Power Consumption:  $\leq 30\text{mA}$ .

Built-in optical tamper alarm technology.

Protective Performance: IP65 (fully-potted), tamper alarm.

Certificate: CE

### Standalone Reader and Controller and Slave Readers

## Specifications

Supply Voltage: 12VDC

Standby Current:  $\leq 30\text{mA}$

Communication Interface: Wiegand26-37

Response Time: 0.1s

Card Reading Range: 3-6cm/2-6cm

Operating Temperature:  $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$

Humidity: 0-95%

Level of Protection: IP65

Antistatic: 15KV

Transmit Distance: 100M

Cable Length: 90-100cm

Dimension: 103mm  $\times$  W48mm  $\times$  H23mm



### Anti-tamper Technology

Built-in light dependent resistor (LDR) for anti-tamper. It will alarm once there is a person unauthorized try to access.